

STAR-FR-UNI



TECHNICAL FEATURES

WIDTH 150 cm (UNI EN 1773/98)

WEIGHT gr/m² 250 (+/- 5%) (UNI EN 5114/82)

WARP ENDS/CM 21 (UNI 8099/80)

WARP COUNT DTEX 630/144 (UNI 8099/80)

WEFT PICKS/INCH 14 (UNI 8099/80)

WEFT COUNT DTEX 630/144 (UNI 8099/80)

COMPOSITION

100% POLIESTERE FR

BREAKING LOAD (UNI EN ISO 13934-1)

WARP 1.500N WEFT 950N

ELONGATION

WARP 48.5% WEFT 40%

SEWING (UNI EN ISO 13936-2)

WARP 180N – 4mm WEFT 180N – 3mm

ABRASION MARTINDALE (UNI EN ISO 12947-2)

30.000 cycles

PILLING (UNI EN ISO 12945-2)

Grade 4 at 2.000 cycles

FIRE REACTION CLASSIFICATION

NFPA 701-10

NFPA 260

BS5852 : 1979

PART 1

M1 (NF P 92-503/92-504/92-505)

CLASS 1 UNI 9177

CLASS 1 UFAC



[FAR Test Report](#)

DO NOT TWIST OR WRING

DO NOT STEAM IRON

