

Go Uni SPECIFICATIONS

Dessin no.	2448	
Fields of application	contract	
Material	100% Trevira cs	
Weight	g/lm	435
	oz/lin.yd	14.03
Width	cm	140
	inches	55
Abrasion resistance	rubs martindale (EN ISO 12947-2)	100,000
	double rubs wyzenbeek (ASTM D4157-07) (heavy duty upholstery)	60,000
Pilling	scale 1-5, max. 5 - EN ISO 12945-2	5
Colour fastness to light	scale 1-8, max. 8 - EN ISO 105-B02	5-8
Colour fastness to rubbing	scale 1-5, max. 5 - EN ISO 105x12 (wet/dry)	4-5/4-5

Maintenance

wash or dry cleaning P(W).
 Go Uni is made of Trevira CS which is a polyester material suited for environments with special requirements for cleaning.
 can be wiped with Virkon S, Actichlor Plus, Prime Source ren-93 or Ethanol (70-85%).
 always follow the manufacturer's instructions and finish by wiping with a damp cloth.
[click here for guidance relating to disinfection.](#)



40°C shrinkage max. 1,5%.



60°C shrinkage max. 2,5%.



74°C shrinkage max. 3,5%.

US ACT

☛ CA TB 117-2013	pass
▣ ASTM D4157-07 Wyz abrasion (heavy duty)	pass
☆ ASTM D3511 Pilling	pass
● AATCC 16 Light fastness	pass
☛ AATCC 8 or 116 Wet/dry crocking	pass

Flammability

- BS 7176 Medium hazard
- BS 5852 Crib 5
- BS 5852 Part 1 0,1 Cigarette & match
- BS EN 1021-1 Cigarette
- BS EN 1021-2 Match
- DIN 4102 B1
- NFP 92-503/504/505 M1
- ÖNORM B 3825-B1-3800-Q1 UK
- Class Uno UNI 9175 Class 1 I EMME
- FAR/JAR 25.853 (a) (i) (ii)

- CA TB 117-2013
- DIN EN 13501-1 B-s1,d0
- Will also pass other flammability standards. Flame retardant performance is dependent upon the foam used.

Environment

Oeko-Tex
EU Ecolabel
Cradle to Cradle Bronze
100% free of heavy metals

Design

Inger Mosholt Nielsen

Colours

Inger Mosholt Nielsen