



Step SPECIFICATIONS

Dessin no.	2440	
Fields of application	contract	
Material	100% Trevira cs	
Weight	g/lm	470
	oz/lin.yd	15.16
Width	cm	140
	inches	55
Abrasion resistance	rubs martindale (EN ISO 12947-2)	100,000
	double rubs wyzenbeek (ASTM D4157-07) (heavy duty upholstery)	100,000
Pilling	scale 1-5, max. 5 - EN ISO 12945-2	4-5
Colour fastness to light	scale 1-8, max. 8 - EN ISO 105-B02	5-7
Colour fastness to rubbing	scale 1-5, max. 5 - EN ISO 105x12 (wet/dry)	4-5/4-5
Maintenance	<p>wash or dry cleaning P(W). Step is made of Trevira CS which is a polyester material suited for environments with special requirements for cleaning. can be wiped with Virkon S, Actichlor Plus, Prime Source ren-93 or Ethanol (70-85%). always follow the manufacturer's instructions and finish by wiping with a damp cloth. click here for guidance relating to disinfection.</p>	
	 <p>60°C shrinkage max. 3%.</p>	
	 <p>74° shrinkage max. 5%.</p>	
US ACT	<ul style="list-style-type: none"> ● AATCC 16 Light fastness ★ ASTM D3511 Pilling ■ ASTM D4157-07 Wyz abrasion (heavy duty) ☞ CA TB 117-2013 ● AATCC 8 or 116 Wet/dry crocking 	<p>pass pass pass pass pass</p>
Acoustic test air flow resistance	<ul style="list-style-type: none"> ● EN 29053 	
Acoustic test sound absorption	<ul style="list-style-type: none"> ● ISO 354 	
Flammability	<ul style="list-style-type: none"> ● IMO MSC 307(88) Annex 1 part 8 ● MED Certificate IMO ● DIN 4102 B1 	

- NFP 92-503/504/505 M1
- BS EN 1021 1&2 Cigarette and Match
- BS EN 1021-1 Cigarette
- BS 5852 Part 1 0,1 Cigarette & match
- BS 5852 Crib 5
- ÖNORM B 3825-B1-3800-Q1 UK
- FAR/JAR 25.853 (a) (i) (ii)
- BS 7176 Medium hazard
- AM 18 - NF D 60-013-(only for fabric)
- CA TB 117-2013
- Class Uno UNI 9175 Class 1 I EMME
- DIN EN 13501-1 B-s1,d0
- Will also pass other flammability standards. Flame retardant performance is dependent upon the foam used.

Environment

Oeko-Tex
EU Ecolabel
100% free of heavy metals

Design

Inger Mosholt Nielsen

Colours

Cenk Kivrikoglu